Docket No.: 3273-0146P

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Canceled)

2. (Currently Amended) A pressure-sensitive adhesive sheet for removal of a solvent-

containing substance by sticking to and peeling off from an article to be cleaned, the sheet

comprising a substrate and a pressure-sensitive adhesive layer, formed at least on one side of the

substrate,

wherein the pressure-sensitive adhesive layer is solid and comprises an adhesive of either

(A) or (B):

(A) an acrylic pressure-sensitive adhesive comprising a base polymer formed by a

base monomer of 40% to 98% by weight, a comonomer of 0% to 50% by weight, and a

functional-group-containing monomer of 0.5% to 15% by weight of the total monomer

components or

(B) a rubber pressure-sensitive adhesive selected from natural rubber pressure-

sensitive adhesives, styrene-butadiene copolymers, polyisobutylene, and styrene-

isoprene-styrene copolymers;

wherein said pressure-sensitive adhesive layer absorbs 5 g/m<sup>2</sup> or more of a solvent

contained in the substance to be removed when the pressure-sensitive adhesive sheet is immersed

Docket No.: 3273-0146P

in the solvent for 1 second, said solvent comprises a mixture of diethylene glycol monobutyl ether acetate and diethylene glycol monobutyl ether [9:1 (by weight)], and wherein the pressure-sensitive adhesive sheet after absorbing 5g/m<sup>2</sup> of the solvent has a tackiness of 3 cN/25-mm or more as determined by a method in conformity with Japanese Industrial Standards (JIS) Z 0237.

3. (Currently Amended) A pressure-sensitive adhesive sheet for removal of a solvent-containing substance by sticking to and peeling off from an article to be cleaned, the sheet comprising a substrate and a pressure sensitive adhesive layer formed at least on one side of the substrate.

wherein the pressure-sensitive adhesive layer comprises an adhesive of either (A) or (B):

- (A) an acrylic pressure-sensitive adhesive comprising a base polymer formed by a base monomer of 40% to 98% by weight, a comonomer of 0% to 50% by weight, and a functional-group-containing monomer of 0.5% to 15% by weight of the total monomer components or
- (B) a rubber pressure-sensitive adhesive selected from natural rubber pressure-sensitive adhesive, styrene-butadiene copolymers, polyisobutylene, and styrene-isorprene-styrene copolymers;

wherein said pressure-sensitive adhesive layer absorbs 5 g/m<sup>2</sup> or more of a solvent contained in the substance to be removed when the pressure-sensitive adhesive sheet is immersed in the solvent for 1 second, said solvent comprises a mixture of diethylene glycol monobutyl ether acetate and diethylene glycol monobutyl ether [9:1 (by weight)], and wherein no stain is

observed in a stainless steel plate (a SUS 430BA plate) by visual inspection when the pressuresensitive adhesive sheet after absorbing 5 g/m<sup>2</sup> of the solvent is stuck to the stainless steel plate by a reciprocating motion of a 2-kg rubber roller and is peeled off from the stainless steel plate.

Docket No.: 3273-0146P

## 4-7. (Canceled)

8. (**Previously Presented**) The pressure-sensitive adhesive sheet for removal of a solvent-containing substance according to claim 2, wherein the pressure-sensitive adhesive layer before use has a tackiness of from 1 to 400 cN/25-mm as determined by a method in conformity with JIS Z 0237.

## 9-21. (**Canceled**)

22. (**Previously Presented**) The pressure-sensitive adhesive sheet for removal of a solvent-containing substance according to claim 2, wherein said acrylic pressure-sensitive adhesive comprises the polymer in adhesive (A) obtained by polymerizing the monomer mixture, and

wherein the base monomer is at least one selected from the group consisting of acrylic  $C_2$ - $C_{10}$  alkyl esters,

the comonomer is at least one selected from the group consisting of methyl acrylate, alkyl methacrylates, vinyl esters, styrenic monomers, and acrylonitrile, and

the functional-group-containing monomer is at least one selected from the group

Docket No.: 3273-0146P

consisting of carboxyl group containing monomers, acid anhydride group containing monomers,

hydroxyl group containing monomers, epoxy group containing monomers, amido group

containing monomers, and amino group containing monomers.

23. (Previously Presented) The pressure-sensitive adhesive sheet for removal of a

solvent-containing substance according to claim 2, wherein said pressure-sensitive adhesive

layer comprises a pressure-sensitive adhesive polymer and a crosslinking agent in the amount of

from 1 to 30 parts by weight relative to 100 parts by weight of the pressure-sensitive adhesive

polymer.

24. (Previously Presented) The pressure-sensitive adhesive sheet for removal of a

solvent-containing substance according to claim 2 or 3, wherein said pressure-sensitive adhesive

layer consists essentially of

the adhesive (A) or adhesive (B), and

at least one additive selected from the group consisting of a crosslinking agent, tackifier,

surfactant, plasticizer, antioxidant, coloring agent, antistatic agent and filler.

25. (Previously Presented) The pressure-sensitive adhesive sheet for removal of a

solvent-containing substance according to claim 2 or 3, wherein said pressure-sensitive adhesive

Docket No.: 3273-0146P

sheet further comprises at least one additive selected from the group consisting of a crosslinking agent, tackifier, surfactant, plasticizer, antioxidant, coloring agent, antistatic agent and filler.

26. (Previously Presented) The pressure-sensitive adhesive sheet for removal of a

solvent-containing substance according to claim 3, wherein the pressure-sensitive adhesive layer

before use has a tackiness of from 1 to 400 cN/25-mm as determined by a method in conformity

with JIS Z 0237.

27. (Previously Presented) The pressure-sensitive adhesive sheet for removal of a

solvent-containing substance according to claim 3, wherein said acrylic pressure-sensitive

adhesive comprises the polymer in adhesive (A) obtained by polymerizing the monomer mixture,

and

wherein the base monomer is at least one selected from the group consisting of acrylic

 $C_2$ - $C_{10}$  alkyl esters,

the comonomer is at least one selected from the group consisting of methyl acrylate, alkyl

methacrylates, vinyl esters, styrenic monomers, and acrylonitrile, and

the functional-group-containing monomer is at least one selected from the group

consisting of carboxyl group containing monomers, acid anhydride group containing monomers,

hydroxyl group containing monomers, epoxy group containing monomers, amido group

containing monomers, and amino group containing monomers.

Application No. 09/936,930 Art Unit 1771 After Final Office Action of March 18, 2005

28. (**Previously Presented**) The pressure-sensitive adhesive sheet for removal of a solvent-containing substance according to claim 3, wherein said pressure-sensitive adhesive layer comprises a pressure-sensitive adhesive polymer and a crosslinking agent in the amount of from 1 to 30 parts by weight relative to 100 parts by weight of the pressure-sensitive adhesive polymer.

Docket No.: 3273-0146P